



PMF

Pneumatische Transfer-Applikationsmaschine
Pneumatic transfer application machine

MOODY
M
INTERNATIONAL
CERTIFICATION
ZERT
Moody Q-Zert GmbH
Zertifiziertes QM-System
DIN EN ISO 9001:2000



970



Technische Details

Indirekter pneumatischer Antrieb

Übertragungskopf 100 x 140 mm mit Schnellwechselsystem für Werkzeughalteplatten

Elektronische Temperaturregelung

Presszeitsteuerung 0 – 10 Sek.

Automatische Bildbahntransport mit Lichtschrankensteuerung über Getriebepbremmotor und pneumatische Bandbremse

Aufspulvorrichtung für verbrauchte Bildbahn

Bildbahnfreigabe über Kurvensystem

Automatischer Schiebetisch 300 x 280 mm mit Zentrierstiften zum Einhängen von Anlegeblechen (Schablonen) und pneumatischen, universell verstellbaren Klemmhaltern

Automatische Sicherheitseinrichtung



Technical Details

Indirect air operated drive

Application head 100 x 140 mm with quick change system for die holding plates

Electronic temperature regulation

Pressing time control 0 – 10 sec.

Automatic tape feed with photocell control over gear brake motor and air operated tape brake

Winding-up device for used tape

Tape release over curve system

Automatic sliding table 300 x 280 mm, with centering pins to hang on guide plates (templates) and with air operated universally adjustable clamping holders

Automatic safety device

