

**WILLCOX & GIBBS**  
**MS[C]T-2604/2614**

Ultra-high speed 1 or 2-needle overlock machines  
with top feed and/or cylinder bed



Sewing

**WILLCOX & GIBBS**



### COMMON SPECIFICATIONS:

Stitch Type:	1 or 2-needle overlock & mock safety stitch (512, 514 stitch)
Max. Sewing Speed:	8000 Stitches/min
Fabric Clearance:	up to 5.5 mm
Needle Gauge (514):	2 mm
Overedge width:	3, 4 & 5 mm

### ADVANTAGE



- Push button stitch regulator
- Lever and micro adjustable differential feed
- Excellent automatic lubrication
- Easy maintenance
- Low noise level
- Best value (quality-price) in the industry

Cylinder bed version

**SPECIFICATIONS:**

**WILLCOX & GIBBS**

Model									
		Max. Sewing Speed S.P.M.	Lifting Of Presser Foot mm	Max. Stitch Length mm	Overedging Width mm	Differential Ratio	Needle	Thread	Thickness Of The Sewn Products
MST-2604-02/833-4	差動上下送 Variable Top Feed	8500	5	3.8	3,4	0.7-2	1	3	中厚-厚 Medium-Heavy
MBC-2604-02/833-4	縮小筒型 Small Cylinder-Bed	8500	5	3.8	3,4	0.7-2	1	3	薄-中厚 Light-Medium
MBC CT-2604-02/833-4	縮小筒型, 差動上下送 Small Cylinder-Bed, Variable Top Feed	8500	5	3.8	3,4	0.7-2	1	3	中厚-厚 Medium-Heavy
MST-2614-M03/M34-2x4	Variable Top Feed	7500	5.5	3.8	3,4	0.7-2	2	4	Medium-heavy
MST-2614-M03C3P2/M34-2x4	pipng seaming	7500	5.5	2.7	3,4,5	.85~2.8	2	4	Medium-heavy
MSC-2614-M03/M34-2x4	Small Cylinder-bed	7500	5.5	3.8	3,4,5	0.7-2	2	4	Medium-heavy
MSCT-2614-M03/M34-2x4	Small Cylinder-bed, Variable Top Feed	7500	5.5	3.8	3,4,5	0.7-2	2	4	Medium-heavy

**OPTIONS:**

- Chain cutter
- Tape cutter
- Automatic foot lift
- Venturi device



**PIMA LLC**  
 PFAFF Industrial of America, Inc.  
 2200 Norcross Parkway, Suite 280A  
 Norcross, GA 30071  
 1-770-447-7545  
[Office@pfaff-industrial.us](mailto:Office@pfaff-industrial.us)  
[www.pfaff-industrial.us](http://www.pfaff-industrial.us)

