

**WILLCOX & GIBBS**  
**MS-2612/2614**

Ultra-high speed 2-needle overlock machines

Sewing

**WILLCOX & GIBBS**



## COMMON SPECIFICATIONS:

Stitch Type:	2-needle overlock & mock safety stitch (512, 514 stitch)
Max. Sewing Speed:	8000 Stitches/min
Fabric Clearance:	up to 7 mm
Needle Gauge:	2 mm
Overedge width:	3, 4, 5 & 6 mm

## ADVANTAGE

- Push button stitch regulator
- Lever and micro adjustable differential feed
- Excellent automatic lubrication
- Easy maintenance
- Low noise level
- Best value (quality-price) in the industry



Direct Drive version

# SPECIFICATIONS:



Model		Max. Sewing Speed S.P.M.	Lifting Of Presser Foot mm	Max. Stitch Length mm	Overedge width mm	Needle Gauge mm	differential ratio	Thickness Of The Sewn Products
MS-2614-01/S34-2x4	Plain Seaming	8000	5	3.8	3,④,5	2	0.7~2	Extra-light-light
MS-2614-M03/M34-2x4	Plain Seaming <standard>	7500	5.5	3.8	3,④,5	2	0.7~2	Medium-heavy
MS-2614SM-M03/M34-2x4/KS 2F	with mini servomotor & materials detector, side Suction Type Thread Trimmer & Venturi Device	7500	5.5	3.8	3,④,5	2	0.7~2	Medium-heavy
MS-2614-M53/M34-2x4	attaching tape	7500	5.5	3.2	3,④,5	2	0.7~2.4	Medium-heavy
MS-2614-54/L44-2x4	attaching tape	6500	7	2.4	④,5,6	2	1.1~3.8	heavy-extra-heavy
MS-2614H-55/H44-3x5	attaching tape	5500	7	3.2	⑤,6	3	1.1~3.8	extra-heavy
MS-2614-83/M34-2x4	Backlatching	7500	5.5	3.8	3,④,5	2	0.7~2	Medium-heavy
MS-2614-24/L44-2x4	serging	6500	7	5	④,5,6	2	0.8~1.5	heavy-extra-heavy
MS-2614-43/M34-2x4	shirring	7000	5.5	3.2	3,④,5	2	0.85~2.8	Medium-heavy
MS-2612-02/M34-2x4	plain seaming	7500	5.5	3.8	3,④,5	2	0.7~2	Medium-heavy

## OPTIONS:

- Chain cutter
- Tape cutter
- Automatic foot lift
- Venturi device



PIMA LLC  
 PFAFF Industrial of America, Inc.  
 2200 Norcross Parkway, Suite 280A  
 Norcross, GA 30071  
 1-770-447-7545  
[Office@pfaff-industrial.us](mailto:Office@pfaff-industrial.us)  
[www.pfaff-industrial.us](http://www.pfaff-industrial.us)

