

WILLCOX & GIBBS
MSA-4830D

3-needle postbed interlock machine

Sewing

WILLCOX & GIBBS



NEW



COMMON SPECIFICATIONS:

Stitch Type:	2, 3- or 4-needle interlock
Max. Sewing Speed:	2000 Stitches/min
Fabric Clearance:	up to 7 mm
Max. stitch length:	4 mm
Needle gauge:	standard 4.8, 5.6 mm and 6.0 mm

ADVANTAGE[®]

- Differential feed
- Dial type stitch regulator
- Excellent automatic lubrication
- Easy maintenance
- Low noise level
- Best value (quality-price) in the industry

SPECIFICATIONS:



Model		 Max. Sewing Speed S.P.M.	 Foot Lift mm	 Needle Gauge mm	 Needle System
MSA-4830-3-156M	General Plain Seaming	2000	7	5.6	UY128GAS
MSA-4830-4-160M	4-Needle,6-Thread,Flat Seaming			6.0	
MSA-4830D-3-156M/UTA1/ST	Direct Drive, Pneumatic Top/Under Thread Trimming	2000	7	5.6	UY128GAS
MSA-4830D-3-156M/UTM/ST	Direct Drive, Electric Top/Under Thread Trimming				



PIMA LLC
 PFAFF Industrial of America, Inc.
 2200 Norcross Parkway, Suite 280A
 Norcross, GA 30071
 1-770-447-7545
Office@pfaff-industrial.us
www.pfaff-industrial.us