

WILLCOX & GIBBS
MSA (MSC)-1390

High Speed 3-needle cylinderbed interlock machine
 High Speed 3-needle small cylinderbed interlock machine

Sewing

WILLCOX & GIBBS



MSA-1390-UTA1

COMMON SPECIFICATIONS:

Stitch Type:	3-needle interlock
Max. Sewing Speed:	5000 Stitches/min
Fabric Clearance:	up to 7 mm
Max. stitch length:	4 mm
Needle gauge:	standard 5.6 mm and 6.4 mm

Model	S.P.M.
MSA-1390-UTA1	5,000
Stitch Length	Needle Bar Stroke
2.3~4.2mm	34mm
Thickness Of The Sewn Products	Foot Lift
MEDIUM~HEAVY	8mm
Needle System	
TV x 5 (#9~#14)	

ADVANTAGE

- Special coating
- Push button stitch regulator
- 34 mm needle bar stroke
- Excellent automatic lubrication
- Easy maintenance
- Low noise level
- Best value (quality-price) in the industry

MSC-1390-UTA1

WILLCOX & GIBBS



Model	S.P.M.	
MSC-1390-UTA1	5,000	
Stitch Length	Needle Bar Stroke	
2.3~4.2mm	34mm	
Thickness Of The Sewn Products	Foot Lift	
Medium~Heavy	8mm	
Needle System		
TV x 5		

It is suitable for chain stitching triple fold on the bottom of jeans, trousers and uniform, etc. The triple folder and automatic presser foot lifter are connected, automatic open/close.

pima

PIMA LLC

PFAFF Industrial of America, Inc.

2200 Norcross Parkway, Suite 280A

Norcross, GA 30071

1-770-447-7545

Office@pfaff-industrial.us

www.pfaff-industrial.us