



CSU-4250

Double Needle, Flatbed Sewing Machine, With Unison Feed. (Large hook).



Model No. CSU-4250		S.P.M. 2,000	
Max.Stitch Length 9mm	Lift Of Foot Presser (Knee) 16mm		
Needle System DP × 17 #22 (#19~#22)	Needle Bar Stroke 36mm		
Alternating Movement 2~5mm			

These machines are equipped with walking foot, needle feed and feed dog, all of which act completely in unison. Consequently, the upper or lower sewing material does not slip and also these machines can sew accurately and easily several sheets of heavy-weight materials piled up together.

- Standard needle gauge: 6.4 mm.
- Automatic lubricating system, smooth and quiet running, easy maintenance.
- Large hook to assure high efficiency, perfect stitch.
- These machines are best suited for sewing tents, seats, cushions, bags, leather products, interior furnishings of automobiles, etc..

CSU-4250



Model:

CSU-4250:

Double Needle, Flatbed Sewing Machine, With Unison Feed. (Large hook)

CSU-4250SM:

Double Needle, Flatbed Sewing Machine, With Unison Feed. (Large hook) (With Smocking Mechanism)

BFT


















Code Description:

BT: Automatic Undertrimming & Automatic Backtacking

BFT: Automatic Undertrimming & Automatic Backtacking & Automatic Presser Foot Lifting

SPECIFICATIONS:

Model No.	 Max. Sewing Speed S. P. M.	 Lifting Of Presser Foot (Knee) mm	 Max. Stitch Length mm	 Needle Bar Stroke mm	 Needle System	 Automatic Presser Foot Lifting	 Automatic Undertrimming	 Automatic Backtacking
CSU-4250	2000	16	9	36	DP×17 #22			
CSU-4250BT	2000	16	9	36	(#19~#22)			
CSU-4250BFT	2000	16	9	36	DP×17 #22			
CSU-4250SM-BT	2000	16	9	36	(#19~#22)			

CSU-4250BFT



Double Needle, Flatbed Sewing Machine, With Unison Feed.(With automatic undertrimming & backtacking & presser foot lifting)(Large hook, for heavy materials)

- Applied with the new style of automatic undertrimming mechanism, the undertrimming result is more perfect.
- Applied with the automatic backtacking device: the backtacking only with gentle press on the backtacking switch, easy operation and could increase the sewing quality & efficiency.
- With Automatic Presser Foot Lifting, easy operation, could increase the sewing efficiency.

CSU -4250SM-BT




Double Needle, Flatbed Sewing Machine, With Unison Feed.(With automatic undertrimming & backtacking, smocking mechanism)(Large hook, for heavy materials)

- Applied with the new style of automatic undertrimming mechanism, the undertrimming result is more perfect.
- Applied with the automatic backtacking device: the backtacking only with gentle press on the backtacking switch, easy operation and could increase the sewing quality & efficiency.
- With Smocking Mechanism, for sewing functional and ornamental seams.



CSU-8671-BFT/LL-1AB

Single Needle, Unison Feed, Flatbed Sewing Machine.
(Automatic Undertrimming & Backtacking, Pneumatic
Presser Foot Lifting,) (Extra Large Hook) (For Heavy Materials)



Model No. CSU-8671-BFT/LL-1AB	S.P.M. 3,500
Max. Stitch Length 6mm	Lift Of Presser Foot (Knee) 20mm
Needle System DP×17#21	Needle Bar Stroke 40mm
Alternating Movement 9mm(Max)	
Operating Space 335×125mm	

The button switch with the immobile function, utilizing the small round button B, could change the function of square button A to touch-control switch C, easy operation. The newly designed undertrimming mechanism, applied with the close up type of lubrication, could decrease the wornout of parts & increase the working efficiency. The special movement mechanism of bobbin case opener (1 stitch, 1 movement stroke), with the slowdown type of closing, could lower strike-sound & avoid the wornout of parts.

- The stitch length is adjustable. The stitch length is adjustable & changeable. With minimum lubrication. The alternating movement of presser foot is adjustable. The alternating movement of presser foot is adjustable & changeable.
- For sewing functional and ornamental seams, preferably on high quality leather goods, seat cover, cushions, bags, tents,etc..

CSU - 867 1 - BFT / L L - 1 AB

Model:

Single Needle, Unison Feed, Flatbed Sewing Machine. (Automatic Undertrimming & Backtacking, Pneumatic Presser Foot Lifting.) (Extra Large Hook)

Code Description:

- 1: Single Needle
2: Double Needle

Code Description:

- B: Automatic Backtacking
F: Pneumatic Presser Foot Lifting
T: Automatic Undertrimming

Optional

- M: Large Hook
L: Extra Large Hook

Code Description:

- S: Max. Stitch Length : 6mm
M: Max. Stitch Length: 8mm
L: Max. Stitch Length: 12mm

Optional

- 1: The Device Of Neat Seam Beginning. (For Upper <needle> Thread)
2: The Device Of Neat Seam Beginning. (For Upper <needle> Thread & Lower <bobbin> Thread)
A: The alternating movement of presser foot is adjustable & changeable. (Second setting, 0~9mm)
B: The stitch length is adjustable & changeable. (Second setting, 0~12mm)

SPECIFICATIONS:

Model No.	Max. Sewing Speed S.P.M.	Lifting Of Presser Foot (Knee) mm	Max. Stitch Length mm	Needle System	Needle Bar Stroke mm	The Alternating Movement of Presser Foot mm	Operating Space mm
CSU-8671-BFT/LS	3500	20	6	DP × 17 #21 (#18~#23)	40	9	335×125
CSU-8671-BFT/LL	3000	20	12		40	9	335×125
CSU-8671-BFT/LS-1AB	3500	20	6	DP × 17 #21 (#18~#23)	40	9	335×125
CSU-8671-BFT/LS-2AB	3500	20	6		40	9	335×125
CSU-8671-BFT/LL-1AB	3000	20	12	DP × 17 #21 (#18~#23)	40	9	335×125
CSU-8671-BFT/LL-2AB	3000	20	12		40	9	335×125
CSU-8672-BFT/LS	3000	20	6	DP × 17 #21 (#18~#23)	40	9	335×125
CSU-8672-BFT/LL	3000	20	12		40	9	335×125
CSU-8672-BFT/LS-AB	3000	20	6	DP × 17 #21 (#18~#23)	40	9	335×125
CSU-8672-BFT/LS-1AB	3000	20	6		40	9	335×125
CSU-8672-BFT/LL-AB	3000	20	12	DP × 17 #21 (#18~#23)	40	9	335×125
CSU-8672-BFT/LL-1AB	3000	20	12		40	9	335×125


CSU-8671-BFT/LL-2AB



Single Needle, Unison Feed, Flatbed Sewing Machine. (Automatic Undertrimming & Backtacking, Pneumatic Presser Foot Lifting.) (Extra Large Hook) (For Heavy Materials)

- The Device Of Neat Seam Beginning.(For Upper <needle> Thread & Lower <bobbin> Thread)
- The alternating movement of presser foot is adjustable & changeable.
- The stitch length is adjustable & changeable.
- Applied with extra large hook, it could reduce the consumption of thread, and increase the sewing efficiency.
- Max. Stitch Length: 12mm

CSU-8672-BFT/LL-1AB



Double Needle, Unison Feed, Flatbed Sewing Machine. (Automatic Undertrimming & Backtacking, Pneumatic Presser Foot Lifting.) (Extra Large Hook) (For Heavy Materials)

- The Device Of Neat Seam Beginning.(For Upper <needle> Thread)
- The alternating movement of presser foot is adjustable & changeable.
- The stitch length is adjustable & changeable.
- Applied with extra large hook, it could reduce the consumption of thread, and increase the sewing efficiency.
- Max. Stitch Length: 12mm